

*One of a kind for lightweight and elastic
3-thread fleece*

MFC 3.2

our performance for your profit



Application:

The MFC 3.2 machine is based on a completely new design concept for perfect 3-thread fleece structures.

In the MFC 3.2, the fleece thread collects the binding thread. In contrast to common procedure, the fleece thread is not positioned in the needle hook. This means there are hardly any limits to the fleece thread's thickness.

The MFC 3.2 is an attractively priced solution when it comes to lightweight and elastic 3-thread fleece fabrics. Its perfect plating results are due to the presentation and laying of the fleece yarn around the needle shaft.

Whenever fabrics for outer wear and sports and leisure wear are needed, the MFC 3.2 is the machine to go with.



- ✓ **Knitting head engineered
by Mayer & Cie. Germany**
- ✓ **High fabric elasticity**
- ✓ **Perfect plating of binding and
ground thread**
- ✓ **Lightweight 3-thread fleece
fabrics**
- ✓ **Convertible into MSC 3.2 II**



The most important facts for you at a glance:

Our feature	Your advantage	Your benefit	Photo/graphic
Knitting head engineered by Mayer & Cie.	Up to 4 needle tracks	Maximum flexibility for SJ and SJ-structures Quality and performance from Mayer & Cie.	
Mechanical take down with integrated folding device	Two take down systems in one	Less down time in case of changeover from one system to the other	
Speedfactor 930 = 31 rpm at 30"	Highest production	Fast return of investment	
Convertible into single jersey machine MSC 3.2 II	Unrivalled flexibility in fabric manufacture	More profit Less competition Higher utilization	

Technical data

Cylinder diameter:	30 - 34
Machine gauges:	20 - 34
No. of feeders:	96 feeders at 30"
Speed up to:	31 rpm at 30" SF 930

Available in selected markets only.

Production example (unfinished)

Structure: 3-thread-fleece 2:1	Efficiency rate: 85,00%	Gauge: 20	Weight: 205 g/m ²
Diameter" 32"	rpm 29	Production m/h 47.9	Production kg/h 23.6
Structure: 3-thread-fleece 3:1 cross + Elastomer plated	Efficiency rate: 85,00%	Gauge: 20	Weight: 325 g/m ²
Diameter 32"	rpm 24	Production m/h 29.7	Production kg/h 19.5



Mayer & Cie.

www.mayercie.com

Mayer & Cie. CN (Changzhou) LLC

Phone: (+86)519-82766660

Zip: 213200

Mail: qingqing.ma@mayercie.com

Address: Building 3, No. 59, Xingming West Rd. Jintan District,
Changzhou City, Jiangsu Province
P.R. China



www.mayercie.cn

Subject to design changes in the interest of technical progress. Illustrations may depict accessories which are not included in the standard machine equipment.